



SPECIFICATIONS

Rated Line Pull	9,500 lbs (4,309 kg) Max
Gear Train System	All Metal Planetary Gear
Reduction Ratio	212:1
Motor	4.8 Hp (3.85 Kw) 12 Volt DC
Winch Line	3/8" x 100' (9.53 mm x 30.48 m) Cable
Overall Dimensions	22.3" x 6.3" x 11" (566 x 160 x 279 mm)
Bolt Pattern	10" x 4.5" (254 x 114 mm)
Shipping Weight	123 lbs (55.8 kg)

K9500EQG



PERFORMANCE OF 1ST LAYER

Line Pull		Line Speed		Motor Current
Lbs	Kgs	Fmp	Mpm	Amp
0	0	19	5.8	110
4000	1816	12.5	3.8	210
6000	2724	10.5	3.2	260
8000	3632	8.6	2.6	300
9500	4313	7.9	2.4	350

LINE PULL & CAPACITY BY LAYER

Cable Layer	Rated Line Pull		Cable Capacity	
	Lbs	Kgs	Ft	Meters
1	9500	4309	15	5
2	7500	3402	38	11.5
3	6200	2812	64	19.5
4	5300	2404	95	29
5	4630	2100	100	30.5

THIS WINCH INCLUDES

- Remote control with 15' of Wire
- 100' Winch Cable With Roller Fairlead & Hook
- All Assembly Hardware
- Colour Coded Power Cables
- Easily Clockable Clutch Handle

ALL WINCHES INCLUDE

THE BEAR ESSENTIALS KIT

